


Liqua Steam

Applications: Universal extraction cleaner for all water-resistant carpets.

Liqua Steam is an all-purpose extraction cleaner which may be used on all fibre types. It contains soil repellent substances that delay resoiling. The product also contains a defoaming ingredient to minimize foam formation. With its high concentration of active ingredients it is extremely cost-effective.

In addition Liqua Steam is also suitable for use in slat cleaning machines (vertical blind cleaning machines).

Liqua Steam is diluted 1:50 with water (200 g Liqua Steam with 10 litres of water) and applied using the extraction method. For heavily soiled areas one can pre-spray using either Traffic Lane Cleaner or Top Action. For individual stains use Fleck Weg.



Standard Specifications:

Structure at 25°C: liquid
pH at 20°C: 11.0 - 12.0 as a concentrate
Density: 1.095 - 1.115 g/cm³

Shelf-Life: 2 years after first opening.

Storage: Frost free. Closed properly. Dry.

Contents (acc. to 648/2004/EG): <5% NTA, <5% nonionic surfactants, <5% anionic surfactants, perfume.

Other contents: Complexing agents, alkalizers, solvents, dye, and water

Biological Degradability: This product fulfills the criteria stated in the EU directive EC 648/2004 concerning detergents.

Article No. 13005

Packaging: Box of 4 x 5L.

Labelling according to Regulation (EU) No. 1272/2008:

None.

Classification according to ADR/RID:

This product is no hazardous material according to transport regulations.

For samples, technical advice and further information please contact::

CEBE Reinigungschemie GmbH • Ruhrstrasse 47 • 22761 Hamburg • Germany

Fon +49(0)40.851 82 - 0 • Fax +49(0)40.851 82 - 29 • Email: info@cebechem.com • www.cebechem.com

These specifications are according to our current knowledge: they are meant to inform about our products and possibilities for their use. No liability may be inferred from this information.